#### JGW-G2314945

# KAGRA

# status and prospects

Tomo Akutsu (NAOJ) for the KAGRA collaboration

# Contents

- Introduction
- Towards O4a
- Beyond O4a
- Summary







### What is KAGRA?

- At Kamioka, Japan
- Constructed under a mountain
- Using cryogenic main mirrors

Ikenoyama 池ノ山 Takahatayama 高幡山

Mozumi Office (Control room)

#### Entrance

### Tunnels excavated 2012-2014 Google



## Heavy snow site

### The interferometer



### KAGRA's run history and plan



## Contents

- Introduction
- Towards O4a
- Beyond O4a
- Summary



8

### **Revisit: O3GK commissioning issues**

800

600

BNS [kpc]

Apr.

#### Sensitivity

 "Time-up" for satisfactory noise hunting before starting O3GK

#### Stability / repeatability

- BNS range drifting
- Frequent lock loss
- Lock acquisition failing due to storms

#### Reliability

- Frost on cryogenic optics  $\rightarrow$  gave up cooling for O3GK
- Unexpected power loss ← beam clipping(?), dead OMC-PD, unused SRM...



K. Kokeyama+, in Proceedings of the 3rd World Summit on Exploring the Dark Side of the Universe (EDSU2020)

Obs start

13th ET symposium (8-12 May 2023, talkhttp://klog.icrr.u-tokyo.ac.jp/osl/?r=5663

### Noise budget estimation right after O3GK

KAGRA collaboration, PTEP ptac093 (2022)



### Upgrading vibration-isolation systems

Not to degrade the GW sensitivity

#### KAGRA collaboration, PTEP ptac093 (2022)

- Inertial damping for main mirror suspensions
- Reduced electronic noise contaminating in the suspension local control
- Damped "overlooked" resonances with improved local sensors/actuators and new optical levers
- Decoupled local DoFs at hardware level as much as possible



13th ET symposium

### Further stray-light mitigation

#### KAGRA collaboration, PTEP ptac093 (2022)

- Installed 14 mid-size baffles around the corner station
- Resolved a crowded optical path (to ISS)
- Additional optical shields
- Additional beam dumps





### Preparation for higher power input

KAGRA collaboration, PTEP ptac093 (2022)



13th EI symposium (8-12 May 2023, talk online)

### **Better stability**

#### Local damping improvement

• Now PRFPMI can be maintained even in somewhat stormy days.

#### Angular-sensing control (ASC)

- Took time for wave-front sensing (WFS) in a strategic way; now WFS can be implemented for some global DoFs; drastically improved the contrast fluctuation.
- In addition, some noise structures and noise floor got better in the sensitivity curve.

#### Doppler phase noise cancellation

• For auxiliary green laser paths; now stable lock acquisition is possible even in somewhat stormy days.



13th ET symposium (8-12 May 2023, talk online)



### **Better reliability**

#### To overcome frosting

- Better vacuum pressure with additional pumps
- Leak check allover the vac chambers thoroughly; took long time to complete.
- Monitors for partial pressures of remnant components
- Defrost heaters
- Re-consider the cooling procedure

#### 1 of 4 main mirrors has been at ~80 K without frosting for ~1 yr.

#### To avoid beam clipping/mis-centering

- Adjusted heights of suspended mirrors basing on measurement for global balancing
- Reliable beam spot target plates
- Additional beam-position monitors/references
- Expanded adjustable height range for the main mirrors when cooled down.
- Implemented beam position control

#### Unlike O3GK, we are not facing:

- Unwanted beam clipping, and
- Superius severe birefringence(?) effects that degrade WFS reliability.







## Avoid unnecessary power loss

#### Transparent SRM

- During O3GK, 30% trans SRM was used, but not doing RSE.
- It has been replaced with a transparent mirror, as we may give up to do RSE during O4(?).

#### Output mode cleaner (OMC) upgrade

- Higher transmissivity: 80% -> 95%
- Fix the broken DCPD -> Double the GW signal
- Revise absolute length





### The latest stable sensitivity



# Contents

- Introduction
- Towards O4a
- Beyond O4a
- Summary

![](_page_17_Picture_5.jpeg)

18

## Towards re-joining 04...

### The strategy is under discussion

- Open some chambers to do additional in-vac works?
- Turn on all the coolers for all the main mirrors?
- Replace with the new higher power laser source and input ~50W?
- Implement better ASC?
- Optimize more the local control?
- (RSE?)

### For O5

- Birefringence in the sapphire crystals will be a problem in the current KAGRA mirrors.
- Search for better crystals was carried out.
- Found that crystals from a Korean company have better birefringence homogeneity compared to the currently installed TMs and comparable absorption.
- We are in a process of making new ITMs with crystals from this company.
- Hopefully, we can install a new set of ITMs before O5.

![](_page_19_Figure_6.jpeg)

## Summary

- KAGRA will join O4a from 24 May to 21 June 2023, and come back to O4 in the spring of 2024 with the better sensitivity.
- Now better sensitivity than that of O3GK is achieved.
- 1 of 4 main mirrors has been at ~80 K for ~1 yr without frosting.
- Despite using the same mirrors as of O3GK, ASC works mostly well; no severe birefringence effects.
- Upgrade plan is under discussion. New ITM preparation is in progress for O5.