


XV ET Symposium | Bologna (26-30 May 2025)

# Risk management critical role: Risk assessment status and risk management evolution



EINSTEIN  
TELESCOPE

Ghada Mahmoud – Systems Engineer /Risk Manager - ETO Project Office  
[ghada.mahmoud@apc.in2p3.fr](mailto:ghada.mahmoud@apc.in2p3.fr)

# Introduction:

---

This presentation focus on the following points:

- Why we perform Risk Management ?
- When were Risk Studies performed in ET by the ETO PO ?
  - The ETO PO Risk Campaign and examples of outcomes  
(note: detailed outcome examples cannot be shared at this time)
  - The ETO Task Force activities
- Additional tools used to support Risk Studies, such as Technology Readiness Level (TRL) assessments and Design Structure Matrix (DSM)

# Why Risk Management ?

Risk management in the Einstein Telescope (ET) is not an “extra step,” but rather a fundamental engineering and governance backbone. It enables structured decision-making within the context of a complex, multi-partner scientific infrastructure project like ET.

Risks are typically assessed based on their potential impact on three critical areas of the project: **cost, schedule, and scope**.

These dimensions are also the foundational constraints of all aspects of project management like cost management and many others.

## Objectives:

- Identify and manage **uncertainties** : Technical, organizational, scheduling, financial, and more.
- Provide a **risk response strategy** that defines how **risks impact cost, schedule, and scope**.
- Support the policy framework for enabling **technology development**.
- Guide **design trade-offs** and informed technology choices.
- Enhance **fundability, credibility, and project resilience**.

# When were Risk Studies performed in ET by the ETO PO ?

Phase	Risk-Related Activity
2024 – 2025	<ul style="list-style-type: none"><li>- <b>ETO PO General Risk Campaign</b> ( starting June 2024 ) : First General structured, collaborative risk campaign across <b>technical groups</b> ( All ISB Subsystems : Interferometer Group , Optics Group, Suspension Group , Vacuum and cryogenics Group, ANM Group; and Engineering Department )</li><li>- <b>It Delivers the First Full Risk Register for ET</b></li><li>- <b>TRL Assessments</b></li></ul>
2025	<ul style="list-style-type: none"><li>- <b>Continuing with the ETO PO General Risk Campaign</b> : Review , other Stakeholders ( ETO ; ETC ; OSB; SCB )</li><li>- <b>ETO Taskforce</b> :<ul style="list-style-type: none"><li>• <b>TRL assessments</b></li><li>• <b>Comparative risk studies</b> between different Configurations of 2L and Triangle Geometries</li><li>• Flexibility (<b>DSM</b> ) and Penalty of change (<b>trade-off analysis between designs and cost impact evaluation</b> ) studies</li></ul></li></ul>
Now	<ul style="list-style-type: none"><li>• Cross-cutting risk integration (identifying, analyzing, and managing risks that affect multiple <b>subsystems, teams, or domains simultaneously</b>)</li><li>• Starting integrating Risks into MBSE ( Jama and 3DX)</li></ul>

## Outcome of the ETO PO General Risk Campaign

- ~200 risks ( **mostly technical** ) identified and assessed across major subsystems (Interferometer, Active Noise Mitigation (ANM), Vacuum & Cryogenics, Optics, Suspension, Engineering Department )
- Risk identification was **strongly collaborated with technical and scientific teams that participated** , ensuring ownership and technical accuracy. The availability and participation of ALL the invited groups should be increased,
- Identification of other systemic risks :
  - Highlighted **critical interdependencies** between subsystems ( Risks caused by **unclear requirement ownership** ).
  - Risks caused by **unclear performance specs**, **undefined interface roles**, and **incomplete design assumptions** .
- Moving from Assessing risks only to transforming **risk mitigations into real design enabler**.

## Example on a Technical Risk from the ETO PO General Campaign causing a trade off

### Risk Description:

A risk that the required specifications for the ET-LF test mass (TM) substrates may not be met.

ET-LF lack of substrate availability in suitable dimensions ( actually 45 cm diameter ) and with suitable optical properties.

### Cause:

The test mass substrates must possess **both large dimensions and exceptional optical characteristics**, including **low optical absorption and low birefringence**.

*At present, materials that meet these criteria (silicon and sapphire ) are not available at the required size and quality.*

*Birefringence is a particularly significant challenge for sapphire.*

### Impact:

If the necessary substrates cannot be procured, the **ET-LF detector may not be constructed according to its current design**.

**This would compromise its ability to meet scientific objectives**, potentially requiring reductions in beam size and TM mass.

### Suggested Mitigations :

- Continue parallel R&D efforts into both silicon and sapphire substrates.
- Conduct trade-off studies to assess the feasibility of tolerating higher optical absorption levels.
- Explore alternative optical layouts that are compatible with smaller mirror sizes.
- Investigate the viability of other materials designs.

Factor	Value
Severity	5 /5
Likelihood	5/5
Overall Risk	High



## Impacts analysis - trade off : example on a cost variation scenario

### Example :

If we suggest reducing the diameter of LF TM from 45 cm to 35 cm ( to give more time for developing R&D ) then the arm length will be maximum 10 KM  
→ we can't construct a 2L configuration for ET with 15 KM armlength ( we will be able to construct 10 KM 2L Configuration instead) and the triangle ET Configuration of 10 KM armlength won't be not affected.

### Example on the cost change :

- Cost Impact : Cost difference of possible 24,98 % reduction of the excavated volumes with respect to the 2025 2L Configuration (15 KM ) one.
- The triangle cost remains unchanged.

The trade off should take into account the impact of the length reduction on the scientific scope, also on the upgradability.

## ETO TaskForce

---

**The ETO Task Force revised the 2024 Einstein Telescope (ET) layout for both the Triangle and 2L configurations to balance cost and performance.**

The updated baseline designs reduce civil infrastructure costs while maintaining scientific objectives and aiming for ensuring flexibility for future development.

A detailed ETO TaskForce study outlines:

- **The design logic**
- **Alternative configurations**
- **Technical risk assessments**



## ETO TaskForce

---

To support a comprehensive technical Risk evaluation, the following risk studies and tools were employed:

- A **Comparative Risk Study** between the 2024 Configuration and the 2025 Task Force Baseline Configuration for both geometries (2L 15 km and Triangle 10 km).
- A **Comparative Risk Study** for Alternative configurations and options for the 2025 Taskforce Baseline
- A **Technology Readiness Level (TRL) Assessment**, followed by a **Technological Risk Study**.
- A **Design Structure Matrix (DSM)** was initiated to analyze system rigidity and interdependencies.
- Several **trade-off scenarios** were analyzed, assessing their cost implications on the overall project.

# Comparative Risk Study


ET		ET-1		ET-2		ET-3		ET-4		ET-5		ET-6		ET-7		ET-8		ET-9		ET-10		ET-11		ET-12		ET-13		ET-14		ET-15		ET-16		ET-17		ET-18		ET-19		ET-20		ET-21		ET-22		ET-23		ET-24		ET-25		ET-26		ET-27		ET-28		ET-29		ET-30		ET-31		ET-32		ET-33		ET-34		ET-35		ET-36		ET-37		ET-38		ET-39		ET-40		ET-41		ET-42		ET-43		ET-44		ET-45		ET-46		ET-47		ET-48		ET-49		ET-50		ET-51		ET-52		ET-53		ET-54		ET-55		ET-56		ET-57		ET-58		ET-59		ET-60		ET-61		ET-62		ET-63		ET-64		ET-65		ET-66		ET-67		ET-68		ET-69		ET-70		ET-71		ET-72		ET-73		ET-74		ET-75		ET-76		ET-77		ET-78		ET-79		ET-80		ET-81		ET-82		ET-83		ET-84		ET-85		ET-86		ET-87		ET-88		ET-89		ET-90		ET-91		ET-92		ET-93		ET-94		ET-95		ET-96		ET-97		ET-98		ET-99		ET-100		ET-101		ET-102		ET-103		ET-104		ET-105		ET-106		ET-107		ET-108		ET-109		ET-110		ET-111		ET-112		ET-113		ET-114		ET-115		ET-116		ET-117		ET-118		ET-119		ET-120		ET-121		ET-122		ET-123		ET-124		ET-125		ET-126		ET-127		ET-128		ET-129		ET-130		ET-131		ET-132		ET-133		ET-134		ET-135		ET-136		ET-137		ET-138		ET-139		ET-140		ET-141		ET-142		ET-143		ET-144		ET-145		ET-146		ET-147		ET-148		ET-149		ET-150		ET-151		ET-152		ET-153		ET-154		ET-155		ET-156		ET-157		ET-158		ET-159		ET-160		ET-161		ET-162		ET-163		ET-164		ET-165		ET-166		ET-167		ET-168		ET-169		ET-170		ET-171		ET-172		ET-173		ET-174		ET-175		ET-176		ET-177		ET-178		ET-179		ET-180		ET-181		ET-182		ET-183		ET-184		ET-185		ET-186		ET-187		ET-188		ET-189		ET-190		ET-191		ET-192		ET-193		ET-194		ET-195		ET-196		ET-197		ET-198		ET-199		ET-200		ET-201		ET-202		ET-203		ET-204		ET-205		ET-206		ET-207		ET-208		ET-209		ET-210		ET-211		ET-212		ET-213		ET-214		ET-215		ET-216		ET-217		ET-218		ET-219		ET-220		ET-221		ET-222		ET-223		ET-224		ET-225		ET-226		ET-227		ET-228		ET-229		ET-230		ET-231		ET-232		ET-233		ET-234		ET-235		ET-236		ET-237		ET-238		ET-239		ET-240		ET-241		ET-242		ET-243		ET-244		ET-245		ET-246		ET-247		ET-248		ET-249		ET-250		ET-251		ET-252		ET-253		ET-254		ET-255		ET-256		ET-257		ET-258		ET-259		ET-260		ET-261		ET-262		ET-263		ET-264		ET-265		ET-266		ET-267		ET-268		ET-269		ET-270		ET-271		ET-272		ET-273		ET-274		ET-275		ET-276		ET-277		ET-278		ET-279		ET-280		ET-281		ET-282		ET-283		ET-284		ET-285		ET-286		ET-287		ET-288		ET-289		ET-290		ET-291		ET-292		ET-293		ET-294		ET-295		ET-296		ET-297		ET-298		ET-299		ET-300		ET-301		ET-302		ET-303		ET-304		ET-305		ET-306		ET-307		ET-308		ET-309		ET-310		ET-311		ET-312		ET-313		ET-314		ET-315		ET-316		ET-317		ET-318		ET-319		ET-320		ET-321		ET-322		ET-323		ET-324		ET-325		ET-326		ET-327		ET-328		ET-329		ET-330		ET-331		ET-332		ET-333		ET-334		ET-335		ET-336		ET-337		ET-338		ET-339		ET-340		ET-341		ET-342		ET-343		ET-344		ET-345		ET-346		ET-347		ET-348		ET-349		ET-350		ET-351		ET-352		ET-353		ET-354		ET-355		ET-356		ET-357		ET-358		ET-359		ET-360		ET-361		ET-362		ET-363		ET-364		ET-365		ET-366		ET-367		ET-368		ET-369		ET-370		ET-371		ET-372		ET-373		ET-374		ET-375		ET-376		ET-377		ET-378		ET-379		ET-380		ET-381		ET-382		ET-383		ET-384		ET-385		ET-386		ET-387		ET-388		ET-389		ET-390		ET-391		ET-392		ET-393		ET-394		ET-395		ET-396		ET-397		ET-398		ET-399		ET-400		ET-401		ET-402		ET-403		ET-404		ET-405		ET-406		ET-407		ET-408		ET-409		ET-410		ET-411		ET-412		ET-413		ET-414		ET-415		ET-416		ET-417		ET-418		ET-419		ET-420		ET-421		ET-422		ET-423		ET-424		ET-425		ET-426		ET-427		ET-428		ET-429		ET-430		ET-431		ET-432		ET-433		ET-434		ET-435		ET-436		ET-437		ET-438		ET-439		ET-440	
----	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--	--------	--



TRL Study

- TRL already provides a **non-contextualized risk score** for technologies.
- However, when placed within the **ET project context**, a structured **risk-based analysis** of TRLs can offer critical insights.
- This approach helps identify **gaps, uncertainties, and dependencies** in technology development.
- It supports the creation of a **realistic and informed development plan**, aligned with ET's technical and scientific goals.

ID	Subsystem / Group	Technology Title	Technology Description	Configuration (Technology)	Global Detector Configuration / Layout	Date	Justification / Reference for Current TRL	Comments for the Actual TRL Level	Actual TRL (Q1 2025)	Expected TRL (for 2029)	R&D Status/ Level (Q1 2025)	Comments on R&D Status	Comments on expected TRL level	Comments ( Please also mention your name beside your comment- Thank you )
	Seismic Isolation and Suspension systems	ET-LF Test-Mass Suspensions	Single cavern suspension system for ET-LF cryogenic test-mass.	Any 12m option. In consideration of the ISB-SUS division's analysis, we only consider "short" suspensions of 12m height - the 17m single-cavern design is	Single Cavern	21/02/2025	<a href="https://www.overleaf.com/read/bqogqgtrdmc#03d933">https://www.overleaf.com/read/bqogqgtrdmc#03d933</a>	Concepts are easy to sketch, using building blocks from existing technologies, but have minimal performance validation and detail.	TRL 2	TRL 3	High	Multiple groups pursuing different concepts.	Technology is extremely complicated, large and expensive. Individual laboratories may only be expected to achieve ≤ TRL 4 without ET project assistance.	(Conor) Actual inertial performance validation will be impossible in short-baseline facilities. Rotational inertial noise may depend on the technical infrastructure. <b>The integration with cryogenic systems is identified as a potential showstopper for several reasons (heat transport, vibration,</b>
	Seismic Isolation and Suspension systems	ET-LF Test-Mass Suspensions	Multi-cavern suspension system for ET-LF cryogenic test-mass.	Any option	Multi-cavern	21/02/2025	Similar to KAGRA test-mass suspension, which exists in a large scale interferometer format, not yet operating under designed cryogenic conditions.	Concepts are easy to sketch, using building blocks from existing technologies, but lack any performance validation or necessary detail.	TRL 2	TRL 3	Low	R&D is part of core commissioning pathway for KAGRA. Fully operational KAGRA would achieve	Best case scenario is KAGRA demonstrates systems integration aspects, but they cannot test the vacuum/ice performance nor the residual motion.	(Conor) KAGRA can test some aspects of systems design and functional integration, but they cannot de-risk performance.
	Seismic Isolation and Suspension	ET-LF CAT5 BB Suspensions	Bottom loaded benches and modular payloads for ET-LF PFM, SEM, BS and short arm Michelson folding mirrors.	Any option	Any	21/02/2025	Based on existing technologies, similar to superattenuator + active platform	Concepts are plausible to sketch, using building blocks from existing technologies, but lack any performance validation or necessary detail.	TRL 2	TRL 4	Low	Design options being explored at Nikhef	Technology is large and expensive. Individual laboratories may only be expected to achieve ≤ TRL 4 without ET project assistance.	(Conor) We expect flow-down of design solutions from the test-mass suspensions to these Cat 5 suspensions. The biggest risk for these suspensions is improper requirements leading to infrastructure limitations.
	Seismic Isolation and Suspension	ET-LF CAT 5 MD Suspensions	Multi-cavern, multiple optic (MO) suspension system for ET-LF LZMI nodes.	Any option	Multi-cavern	21/02/2025	Based on existing technologies, similar to superattenuator + active platform	Concepts are easy to sketch, using building blocks from existing technologies, but lack any performance validation or necessary detail.	TRL 2	TRL 4	Low	Design options being explored at Nikhef	Technology is large and expensive. Individual laboratories may only be expected to achieve ≤ TRL 4 without ET project assistance.	(Conor) We expect flow-down of design solutions from the test-mass suspensions to these Cat 5 suspensions. The biggest risk for these suspensions is improper requirements leading to infrastructure limitations.
	Seismic Isolation and Suspension	ET-LF CAT4 TB Suspensions	Top loaded benches and modular payloads for ET-LF IMC, SQI and INJ nodes.	Any option	Any	21/02/2025	Based on existing technologies, similar to superattenuator + active platform	Concepts are plausible to sketch, using building blocks from existing technologies, but lack any performance validation or necessary detail.	TRL 2	TRL 4	Low	None ongoing.	Technology is large and expensive. Individual laboratories may only be expected to achieve ≤ TRL 4 without ET project assistance.	(Conor) Requires input from IFD experts to determine residual motion requirements. Improper requirements are a significant risk.
	Squeezing	meter-size periscope	(suspended?) periscope able to shift the optical plane by about 2-2.5 m while maintaining tight stability requirements	Not applicable	LF: FC in tunnel, only if in different level HF: FC in tunnel, in any case	21/02/2025	cm scales periscope are implemented in Virgo/LIGO. 2 m scale periscope technology not yet defined	Significant size difference vmt that has been previously studied	TRL 1	TRL 2	Low	Occasional discussion		
	Squeezing	beam(-pipe) crossing	SQZ beam and vacuum pipe has to intersect with FC vacuum (between BS and ITM)	Not applicable	LF FC in tunnel @ ITF level	21/02/2025	Technology identified, vacuum constraints should be studied	Not commonly (never) done. Cna have some of vacuum contamination, stray light...	TRL 2	TRL 2	Zero			
	Squeezing	Finesse tuning	Implement a coupled cavity to use the tuning of the first cavity to control the overall finesse	Variable finesse with 3-mirror cavity	3-mirror FC	21/02/2025	Simulation in progress, grant submitted for founding R&D	Concept not sufficiently developed, even on paper	TRL 2	TRL 2.5 (if grant approved)	Low			
	Squeezing	Finesse tuning	Controlling the FC IM reflectivity by tuning ethalon effect with temperature	Variable finesse with ethalon	2-mirror FC	21/02/2025	10.3390/galaxies8040080	Used in Virgo, but a design matching ET FC requirements has not been studied	TRL 3	TRL 3	Low			
	Squeezing	Finesse tuning	Change the cavity finesse by replancing cavity mirror(s)	Variable finesse with mirror replacement	2-mirror FC	21/02/2025	Idea plausible should be defined a method with suspension/vacuum group to do it fastly	Can be done for sure, but concept of how to do it "conveniently" (low risk/fast operation) has not been studied	TRL 2	TRL 2	Zero			
	Squeezing	Stray light control in FC (beampipe size)	A sufficient baffling strategy (number and size) must be developed to ensure stray light is	Not applicable		21/02/2025	<a href="https://arxiv.org/abs/2307.14104">https://arxiv.org/abs/2307.14104</a>	More detailed stray-light studies are needed to confirm FC beampipe inner diameter (adaptation of work done for arm)	TRL 2	TRL 2	Moderate			
	Cryogenics	Central helium cryoplant with transfer system	State-of-the-art technology in large-scale experimental physics, e.g. LHC	Underground coldbox, central service cavern, providing cooling power to all consumers in a vacuum any			<a href="https://iopscience.iop.org/article/10.1088/1757-899X/12401012095">https://iopscience.iop.org/article/10.1088/1757-899X/12401012095</a> ET-0605A-24	Necessity of seismic isolation of the coldbox vs. distance t.b. investigated	TRL 5	TRL 7	Moderate	Measurements at CERN and KEK	Modeling of coldbox isolation requirements	
	Cryogenics	Individual pulse tube cryocoolers	State-of-the-art technology implemented e.g. in KAGRA	Individual plants were to consider power dissipation cavern, additional noise (compressors in noisy rooms) any			KAGRA paper...	Not scalable to ET requirements, in particular regarding cryopumps	TRL 5	TRL 7	High			We may not use this technology in ET
	Cryogenics	Sorption cooling with LN2	LN2 distribution system and 3-stage sorption cooling system with Ne, H2 and He	Only for payloads and cryostats, not for cryopumps	Any		ET-0605A-24 (ET Pathfinder)		TRL 2	TRL 7	Moderate	Ongoing activity @NIKHEF	this will be for a prototype at smaller scale.	Scalability for ET-requirements not yet demonstrated





TRL Level								
Identify the stage of development			Check for component testing		Look for prototype testing in real-world		Assess readiness for deployment	
1	2	3	4	5	6	7	8	9
Initial Research	Concept Development	Experimental Testing	Component Validation	Integrated Technology Testing	Prototype Demonstration in Relevant Setting	Operational Environment Testing	Final Product Testing	Real-World Deployment

# What Changed : (2025 ETO TaskForce Configuration- 2L and Triangle )

- LF Squeezing FCs in X arm with Periscope (2m heigh for 2L ; 4m for Triangle ) routed through the LSEM Tower to the LSQI Tower
- HF Squeezing FC in Y arm with Periscope directly routed to the HSQI Tower
- 2- Mirror FC with reduced pipe diameter from 1m to 650 mm
- Reduced Length of LF IMC from 300 m to 120 m
- Merging HF IMCs in same tunnel
- Route BHD through BS in LF Ifo
- Other reshuffling in central area to adapt to the new changes
- Reduced LF TM susp heigh from 17 m to 13 m
- Reduced Tower height for other HFI Optics
- Reduced footprint of CAT1 Benches

## Alternative Options :

- Double Cavern
- No periscope for LF\_FC
- Alternative routing for SQZ beam
- Bow-tie IMC
- Reduced tower heigh for HF TM
- Reduced Tower height for LFI Optics
- Reduced Cryostat size



# Risks and impact analysis in the TaskForce

## Infrastructure-Based Mitigations

**Pros:** Often straightforward and effective.

**Cons:** Can involve **higher upfront costs**

## No-Cost Mitigations with Trade-Offs

**Pros:** Lower cost.

**Cons:** could introduce **new technical risks or limitations**.

## Systems Design Changes and R&D-Based Mitigations

**Pros:** Can lead to innovative, long-term solutions.

**Cons:** Typically require **additional time, cost, and resources**, and may introduce **schedule delays**.



# LF Squeezing FCs in X arm with Periscope (2 m heigh for 2L ; 4 m heigh for Triangle ) routed through the LSEM Tower to the LSQI Tower

**Risk Description:**

Risk of degraded squeezing,

Using a **tall (2 m or 4 m ) periscope** in the ET-LF filter cavity introduces **phase noise** into the squeezed light. This **degrades the squeezing** injected into the interferometer, especially at low frequencies where ET-LF is most sensitive.

**Cause:**

The periscope can:

- **Vibrate or flex**, leading to **mechanical instability** → should cause **mirror misalignment**
- Introduce **phase fluctuations** in the squeezed beam path

These effects result in **decoherence** or **loss of squeezing**.

**Impact:**

- Reduced squeezing means **higher quantum noise** → **lower sensitivity** of ET-LF.
- This is **more severe at low frequencies** (<30 Hz), which are critical for detecting **massive black hole mergers**.

**Suggested Mitigation**


1. **Remove the Periscope**

The best mitigation is **architectural**: Place the **ET-LF interferometer and its squeezing/filter cavity on the same horizontal plane** (**Less Risky – Trade off scenarios ( from less costly to more costly )** )


2. **Prototype Testing** (Mechanical stability, Impact on squeezing ) (**More Risky – Delay - Cost** )

Before ruling out periscopes entirely : **Implement a periscope** in an existing gravitational-wave detector .



This helps assess whether periscopes could be made stable enough with special materials or isolation systems.



## 2024 2L Configuration



## 2025 ETO TaskForce 2L Configuration



Factor	Value 2L	Value Triangle
Severity	5/5	5/5
Likelihood	3/5	4/5
Overall Risk	High	High
Applies to	ET-LF mainly	ET-LF mainly
Less impact on	ET-HF	ET-HF



## Example – trade off. Cost vs risk minimization



2025 Triangle configuration but considering the 2024 configuration for the LF Filter Cavity ( No periscope for LF FC - no change in HF FC )

Cost Impact : Cost difference of possible **+16, 24 % increase** of the excavated volumes with respect to the 2025 Triangle Configuration one.

2025 2L configuration but considering the 2024 configuration for the LF Filter Cavity ( No periscope for LF FC - no change in HF FC )

Cost Impact : Cost difference of possible **+14, 01 % increase** of the excavated volumes with respect to the 2025 2L Configuration one.

Trade off should be analysed between a cost increase and the risk minimization for the performances of the squeezing cavity



**Alternative design options** : No Periscope for LF\_FC , the LF\_FC is in the main tunnel and is directly routed from the Beam Splitter

Factor	Value 2L and Triangle
Severity	2/5
Likelihood	5/5
Overall Risk	High

**Impact or Risk Description:**

Increase the astigmatism in the y arm recycling arm. Risk not to find a suitable configuration in the design.


**Cause:**

Movement of the mirror LZM2\_Y to allow passage of SQI  $\rightleftharpoons$  SQZ beam through Beam Splitter

### Suggested Mitigation

## Optimizing the optical design of the telescope - use of freeform optics

Two scenarios for not considering the periscope in LF : one introduce a risk of astigmatism ( to be mitigated ) and one does not increase the astigmatism ( but increase the cost)



## Reduced Length of LF Input Mode Cleaner from 300 m to 120 m

### Impact or Risk Description:

If the IMC is **too short (120 m instead of 300 m)**, it may **not effectively filter out high-frequency and high-amplitude noise** in the laser beam. This noise then enters the main interferometer and **compromises the sensitivity** of the detector.  
Risk of not be able to implement the design mitigation strategies to maintain the cleaner performance.

### Cause:

A shorter IMC:

- Has less **optical path** to average out fluctuations
- Cannot suppress high-frequency noise as well
- Is less effective at stabilizing the beam's **phase, amplitude, and geometry**

### Impact:

- Frequency noise** from the laser isn't fully removed
- Amplitude noise** remains, adding false signals
- These noise sources enter the **main interferometer**

### Suggested Mitigation

#### Use a High-Finesse IMC


This comes at a cost:

- More complex control systems** are needed
- Thermal and optical losses** are more sensitive
- The system becomes **harder to stabilize and maintain**


So, while it reduces the risk, it introduces new technical challenges. ( Delay )

Factor	Value 2L and Traingle
Severity	5/5
Likelihood	2/5 – 3/ 5 cost of the trade off
Overall Risk	High
Applies to	ET-LF mainly

## 2024 2L Configuration



## 2025 ETO TaskForce 2L Configuration



## Example - trade off : cost vs detector performance

**2025 Configuration Triangle + 300 m LF Input Mode Cleaner instead of 120m**

Cost Impact : Cost difference of possible **+1, 31 % increase** of the excavated volumes with respect to the 2025 Triangle Configuration one.

**2025 Configuration 2L + 300 m LF Input Mode Cleaner instead of 120 m**

Cost Impact : Cost difference of possible **+0, 81 % increase** of the excavated volumes with respect to the 2025 2L Configuration one

Trade off to be analysed between the cost increase and the IMC performance (to be evaluated)

## Reduced LF TM susp heigh from 17 m to 13 m

**Risk Description:**

Risk of not find a suitable design fulfilling the LF TM suspension requirements, due to the cavern height available (13m tall LF TM suspension)

**Cause:**

The actual performance of the suspension is not compliant with the design one (i.e.: not enough pendulum length to observe from 1 Hz to 3 - 4 Hz)

**Impact:**

Underperforming detector; Reduced scientific reach in the critical 1–10 Hz band

**Suggested Mitigation**

Keep an adequate safety margin (can be going to 5m) on the caverns height / Update the design adding some active seismic filtering ( platform)

Factor	Value
Severity	5/5
Likelihood	2/5 ( the likelihood depends on both the science objective (LF) and the decision on the heigh of the cavern ) the likelihood may increase to 3 or 4
Overall Risk	High
Applies to	ET-LF mainly / TM

## Trade off : cost vs risk mitigation

**2025 Configuration Triangle + 12 Caverns are affected : LF TM Cavern : 5m safety margin ( + 3 m )**

Cost Impact : Cost difference of possible **+0,78 % increase** of the excavated volumes with respect to the 2025 Triangle Configuration one

**2025 Configuration 2L + 8 Caverns are affected : LF TM Cavern : 5m safety margin ( + 3 m )**


Cost Impact : Cost difference of possible **+0,42 % increase** of the excavated volumes with respect to the 2025 Triangle Configuration one

Trade off between cost increase and minimization of the risk associated to the suspensions system technical design

## Outlook

- **The ETO PO Risk Campaign will be continued, involving different identified and selected stakeholders**
- **DSM and TRL analysis will be expanded out of the TaskForce context**
- **For professional risk management and risk traceability the risk data will be inserted in JAMA and 3DX in collaboration with Aachen University**






XV ET Symposium | Bologna (26-30 May 2025)




EINSTEIN  
TELESCOPE

# Thank you !

## 2024 Triangle Geometry - Configuration



## 2025 Triangle Geometry - Configuration



## Reduced footprint of CAT1 Benches

**Risk Description:**

The optical Layout ( Flexibility of choice ) is limited by the super-attenuators capacities / Design no mature

**Cause:**

Unable to locate sub-modular suspended optics within a single interferometer node.

**Impact:**

Reduced flexibility for optical layout.

**Suggested Mitigation**

Significant R&D needed to understand IF it is possible to colocate sub-modularly suspended optics within a single node / May need to Redesign suspension or split the optics into two groups with the seperate vacuum

Factor	Value
Severity	4/5
Likelihood	5/5 (Likelihood depends on the results of the R&D needed to verify if we can colocate more optics on the suspended benches)
Overall Risk	High

**Alternative options analysis : Bow-Tie IMC**

**Risk Description (design not mature):**

Use of bow-tie cavity induced shorter tunnel length / No demonstration of long bow-tie cavity for IMC

**Cause:**

4 mirrors cavities allows more compact IMC / All current interferometers use linear 3 mirrors cavities for IMC

**Impact:**

Limitation of the upgradability if tunnel too short. Not possible to go back to linear 2 cavities. / Degradation of the input beam quality, low transmission due to higher losses

**Suggested Mitigation**

Optical simulations of the performances

Factor	Value
Severity	4/5 – 5/5
Likelihood	4/5 – 3/5
Overall Risk	High

## Alternative options analysis : Reduced Cryostat size

**Risk (design not mature) :**

Risk of Not having enough space for the attenuation system within the integrated tower - Reducing the cryostat size reduce the performance of the cryogenic

**Cause:**

Reducing the cryostat size limits thermal shielding, increases heat load density, restricts cryocooler capacity, and reduces space for vibration isolation and suspension systems

**Impact:**

This leads to higher thermal noise, reduced cooling efficiency, increased mechanical vibrations, and overall degradation of detector sensitivity

**Suggested Mitigation**

Redesign and Prototype of the cryostat ( and maybe the integrated tower ) - Reducing size is possible if the design / prototyping / testing are took into consideration , it requires an adapted design to increase the performance ( R&D )

Factor	Value
Severity	4/5
Likelihood	5/5
Overall Risk	High

**Alternative options analysis : Double Cavern ( TM LF)**

**Issue:**  
Increase in cost

**Cause:**  
the construction of double cavern / and the access to the top cavern is technically more complex and increase the cost because it needs additional volume to be excavated

**Comment**  
Double cavern or compact cryostat is the solution for Mechanical Interference between inverted pendulum and cryostat Affecting the sensitivity due to vibrational noise especially in the low frequency

Factor	Value
Severity	3/5
Likelihood	4/5
Overall Risk	High